



- .1 סאונד חזק ואיכותי במיוחד משולב מיקרופון.
- .2 48k OPUS Audio Coder - מאפשר איכות צליל מעולה.
- .3 מתממשק ל: SIP, (IPPBX, IP Phone), VoIP
- .4 מתממשק ל- ONVIF IP Camera דרך VMS
- .5 תמיכה בהודעות מוקלטות מראש.
- .6 תמיכה ב-HPPT API תמיכה מערכות אזעקה

### מפרט טכני

#### Audio

Codec OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz

#### Speaker

Max SPL	96dB	Harmonic Distortion	0.1@1kHz
Frequency Response	100Hz~18KHz	Signal to Noise Ratio	91dB
Frequency Range	500-2KHZ +-10dB 400-12KHZ +-20dB		

#### Network

Security:	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
VoIP	Support for SIP protocol for integration with VoIP systems, intergrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA

#### Amplifier

Amplifier Description Built-in 15W Amplifier

#### General

Operating Temperature	'-30°C — +60°C	Installation	In ceiling
Operating humidity	5%-85%	Dimensions	200x90mm
Rate Power	15W	Net Weight	1 KG
Power Supply	PoE or 12-24V	Languages	English