



מפרט טכני

- .1 סאונד חזק ואיכותי במיוחד.
- .2 48k OPUS Audio Coder - מאפשר איכות צליל מעולה.
- .3 מתממשק ל: SIP, (IPPBX, IP Phone), VoIP
- .4 מתממשק ל- ONVIF IP Camera דרך VMS
- .5 תמיכה בהודעות מוקלטות מראש.
- .6 תמיכה ב-HPPT API תמיכה מערכות אזעקה

Audio

Codec OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz

Speaker

Max SPL	96dB	Harmonic Distortion	0.1@1kHz
Frequency Response	100Hz~18KHz	Signal to Noise Ratio	91dB
Frequency Range	500-2KHZ +-10dB 400-12KHZ +-20dB		

Network

Security: Password protection, IP address filtering, Digest authentication, User access log, firewall

Network Protocol SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP

Network Interface 10/100 Base-TX, RJ45

VoIP Support for SIP protocol for integration with VoIP systems, intergrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA

Amplifier

Amplifier Description Built-in 15W Amplifier

General

Operating Temperature	'-30°C — +60°C	Installation	In ceiling
Operating humidity	5%-85%	Dimensions	200x90mm
Rate Power	15W	Net Weight	1 KG
Power Supply	PoE or 12-24V	Languages	English