



מפרט טכני

1. סאונד חזק ואיכותי במיוחד.
2. עמיד למים IP67 להתקנה בחוץ.
3. מתממשק ל-48k OPUS Audio Coder מאפשר איכות צליל מעולה.
4. מתממשק ל: SIP, (IPPBX, IP Phone), VoIP.
5. מתממשק ל-ONVIF IP Camera VMS דרך ONVIF.
6. תמיכה בהודעות מוקלטות מראש.
7. תמיכה ב-HPPT API.

Audio

Codec OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz

Speaker

Max SPL	120dB	Harmonic Distortion	0.1@1kHz
Frequency Response	350Hz~8KHz	Signal to Noise Ratio	91dB
Frequency Range	500-2KHZ +-10dB 400-12KHZ +-20dB		

Network

Security:	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
VoIP	Support for SIP protocol for integration with VoIP systems, intergrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA

Amplifier

Amplifier Description	Built-in 30W Amplifier	Power Supply	PoE or 12-24V
-----------------------	------------------------	--------------	---------------

General

Operating Temperature	'-30°C — +60°C	Installation	Wall Mounted
Operating humidity	5%-85%	Dimensions	285*205*290mm
Material	ABS (IP67 water-proof)	Net Weight	2 KG
Rate Power	30W	Languages	English